TRUE MANUFACTURING CO., INC. ® U.S.A. FOODSERVICE DIVISION	Project Name:	
B U.S.A. FOODSERVICE DIVISION	Location:	
2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546	Item #: Qty:	SIS #
Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com	Model #:	
Model: FLM-81~TSL01 Full Length Merchandiser: Swing Door Refrigerator with Hydroco	arbon Refrigerant~True Standard Look Vers	ion 01
	FLM-81~TSL	D1
	The world's #1 manufacturer of merchandisers.	glass door
<image/>	 Factory engineered, self-contain capillary tube system using environmentally friendly R290 H carbon refrigerant that has zero depletion potential (ODP), & 0.0 warming potential (GWP). High capacity, factory balanced refrigeration system holds 33°F (.5°C to 3.3°C) for best food presextreme conditions. Exterior - non-peel or chip black coated cold rolled steel ends wi aluminum cabinet top and back and permanent. Interior - attractive, white alumi interior liner with stainless steel Double pane thermal insulated swing doors. Black powder coat Full length doors for maximum capacity. Self closing doors. Positive seal, type closure system. 	nydro (0) ozone (2) global , to 38°F servation in k powder ith black k; durable inum floor. glass ted. product
Exterior Color Options	LED interior lighting provides m lighting throughout the cabine shielded.	
	 Entire cabinet structure is foam place using a high density, poly insulation that has zero ozone or potential (ODP) and zero global potential (GWP). 	urethane depletion
	Bottom mounted units feature	
	"No stoop" lower shelf to maxin product visibility.	lize

- Storage on top of cabinet.
- Easily accessible condenser coil for cleaning.

AIA #

ROUGH-IN DATA

Standard Black Exterior

Specifications subject to change without notice. Chart dimensions rounded up to the nearest %" (millimeters rounded up to next whole number).

			Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)	
Model	Doors	Shelves	W	D†	Н	HP	Voltage	Amps	Config.	((kg)
FLM-81~TSL01	3	12	80¾	30¾	79	3⁄4	115/60/1	6.3	5-15P	9	810
			2051	772	2007	N/A		N/A		2.74	368

Optional Stainless Exterior

Optional White Exterior

† Depth does not include 1%" (42 mm) for door handles.

INTERIOR ATTON	APPROVALS:	AVAILABLE AT:	
4/24 Printed in U.S.A.			

Model:

FLM-81~TSL01

Full Length Merchandiser:

Swing Door Refrigerator with Hydrocarbon Refrigerant~True Standard Look Version 01



STANDARD FEATURES

DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, and lower utility costs in an attractive merchandiser that brilliantly displays packaged food and beverages.

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Bottom mounted condensing unit positioned for easy maintenance. "No stoop" lower shelf maximizes visibility by raising merchandised product to higher level.

CABINET CONSTRUCTION

- Exterior non-peel or chip black powder coated cold rolled steel ends with black aluminum cabinet top and back; durable and permanent.
- Interior attractive, white aluminum liner with stainless steel floor.

- Insulation entire cabinet structure is foamedin-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- Welded, heavy duty steel frame rail, black powder coated for corrosion protection.
- Frame rail fitted with leg levelers.

DOORS

- Double pane thermal insulated glass swing doors with black powder coated frames.
- Door sign decal. Variety of decal options available.
- Each door fitted with 12" (305 mm) long extruded handle.
- Self closing doors. Positive seal, torsion type closure system.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

SHELVING

- Twelve (12) adjustable, solid white powder coated cantilever shelves, adjustable for up to 15° tilt in 5° increments. Three (3) white PVC coated wire floor racks.
- Shelves are 24½ "L X 21"D (623mm x 534 mm). Floor racks are 22½ "L X 20½ "D (575mm x 591mm)

LIGHTING

 LED interior lighting provides more even lighting throughout the cabinet. Safety shielded.

MODEL FEATURES

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- See our website www.truemfg.com for latest color and sign offerings.

- Convenient clean-out drain built in cabinet floor.
- NSF/ANSI Standard 7 compliant for open food
 - product.

ELECTRICAL


 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.





OPTIONAL FEATURES/ACCESSORIES

Upcharge and lead times may apply.

- U White exterior.
- □ Stainless steel exterior.
- Black aluminum interior liner with black shelving.
- Clear aluminum interior liner.
- □ Stainless steel interior liner.
- □ 4" (102mm) stemmed castors.
- □ All left hinge doors.
- All right hinge doors.
- U Wired cantilever shelves.
- Barrel locks located in grill assembly (requires one per door)
- Additional shelves.
- □ Product ID strips on shelves and floor racks.
- □ TrueFlex bottle organizers available with Wired cantilever shelf option.







METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

=							
	KCL	Model	Elevation	Right	Plan	3D	Back
		FLM-81~TSL01					

TRUE MANUFACTURING CO., INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com

PLAN VIEW