

## **USA FOODSERVICE DIVISION**


True

# TBR36-RISZ1-L-B-S-1

True Bar Refrigerator • Reach-in single zone refrigerator

| Project Name | Location | Item # | Quantity | Model # | AIA # | SIS # |
|--------------|----------|--------|----------|---------|-------|-------|
|              |          |        |          |         |       |       |

## FEATURES



- Temperatures of 33°F to 38°F (.5°C to 3.3°C).
- Exterior: Black powder coated cold rolled steel with stainless steel countertop.
- · Interior: Stainless steel.
- True's self-cleaning RCU technology eliminates the need to clean the condenser coil, reduces energy consumption and helps maintain the coldest temperatures and freshest product.
- · White LED lighting.
- NSF/ANSI standard 7 compliant for open food product.
- UL Rated for outdoor use.
- Three (3) interior access ports.
- · Field reversible doors.
- Zero clearance (side and back).
- Front air intake / front air discharge.
- Electronic temperature control with exterior digital display.

## **ROUGH-IN DATA**

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

|                     | Doors | Shelves | Capacity  12 oz. Cans 12 oz. Bottles | Cabinet Dimensions<br>(inches)<br>(mm) |     | 115V/60/1<br>Voltage |     | Cord<br>Length‡ | Crated |       |                          |                       |
|---------------------|-------|---------|--------------------------------------|--|-----|----------------------|-----|-----------------|--------|-------|--------------------------|-----------------------|
| Model               |       |         |                                      | 12 oz. Bottles                         | w   | D†                   | н   | HP              | Amps   | NEMA  | (total ft.)<br>(total m) | Weight (lbs.)<br>(kg) |
| TBR36-RISZ1-L-B-S-1 | 1     | 3       | 44 6-pks                             | 27 6-pks                               | 36  | 24%                  | 34¾ | 1/5             | 1.8    | 5-15P | 10                       | 285                   |
|                     |       |         |                                      |  | 914 | 631                  | 881 |                 |        |       | 3.04                     | 130                   |

† Depth does not include 1½" (35 mm) for door handles. \*Height does not include ¼" (7 mm) for leg levelers.

 $\ddagger$  Cord length listed represents usable cord length.















## **USA FOODSERVICE DIVISION**

## TBR36-RISZ1-L-B-S-1

True Bar Refrigerator • Reach-in single zone refrigerator

### ADDITIONAL FEATURES

### **Refrigeration System**

- Factory engineered, self-contained, capillary tube system.
- · Environmentally friendly R290 hydrocarbon refrigerant.
- Forced air refrigeration system which maintains 33°F to 38°F (.5°C to 3.3°C) product temperatures.
- True's self-cleaning RCU technology eliminates the need to clean the condenser coil, reduces energy consumption and helps maintain the coldest temperatures and freshest product.

#### **Cabinet Construction**

- Exterior: Black, powder coated cold-rolled steel with stainless steel countertop.
- Interior: Stainless steel floor and sides with ABS plastic ceiling.
- Insulation: Entire cabinet is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion and zero global warming potential.
- · Base fitted with leg levelers.

#### **Doors**

- · Door locks standard in countertop.
- Field Reversible Doors standard (reverse hinge kit included).

#### Shelving

- Three (3) adjustable, gray PVC coated wire shelves. 19%" W x 18" D (499 mm x 458 mm). Four (4) polished stainless steel shelf clips included per shelf.
- Aluminum shelf support pilasters. Shelves are adjustable on ½"
   (13 mm) increments.

#### **Model Features**

- NSF/ANSI Standard 7 compliant for open food product.
- · UL approved for outdoor use.
- Electronic temp control with exterior digital display.
- Three (3) access ports standard (see drawing for locations).

#### **Electrical**

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.


### **Optional TBR Features/Accessories**


(upcharge and lead times may apply)


- ☐ Castors 7/8"H (23 mm) rollers, 2"D (51mm), 3"D (77mm), 4"D (102mm), 5"D (127mm) castors
- ☐ 6"H (153mm) legs
- ☐ 6"H (153mm) seismic legs
- ☐ Alternative temperature zones available (55° red wine, 45° white wine)
- ☐ Right side compressor
- ☐ Shelving (wine, cut-out, additional standard wire, available in black or gray)
- ☐ Bottle Organizers (available in black or gray)
- ☐ Additional Access Ports


## PLAN VIEWS

Plan View Notes: Dimensions in brackets are in millimeters. • Depth does not include 1½" (35 mm) for door handles. • Height does not include ¼" (7 mm) for leg levelers.









FRONT VIEW SIDE VIEW

**BACK VIEW** 

**TOP VIEW**