


USA FOODSERVICE DIVISION

TBR52-RISZ1-L-S-GG-1

True Bar Refrigerator • Reach-in single zone refrigerator

Project Name	Location	Item #	Quantity	Model #	AIA#	SIS#

FEATURES



- Temperatures of 33°F to 38°F (.5°C to 3.3°C).
- · Exterior: Stainless steel.
- · Interior: Stainless steel.
- True's self-cleaning RCU technology eliminates the need to clean the condenser coil, reduces energy consumption and helps maintain the coldest temperatures and freshest product.
- TruLumina® LED interior lighting.
- NSF/ANSI standard 7 compliant for open food product.
- · UL Rated for outdoor use.
- Three (3) interior access ports.
- Field reversible doors.
- Zero clearance (side and back).
- Front air intake / front air discharge.
- Electronic temperature control with exterior digital display.

Titua,

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

			Cap	acity	Cabinet Dimensions (inches) (mm)		115V/60/1 Voltage			Cord Length‡	Crated Weight (lbs.)	
Model	Doors	Shelves	12 oz. Cans	12 oz. Bottles	w	D†	н	HP	Amps	NEMA	(total ft.) (total m)	(kg)
TBR52-RISZ1-L-S-GG-1	2	6	78 6-pks	49 6-pks	52	24%	34¾	1/5	1.8	5-15P	10	365
					1321	631	881				3.04	166

† Depth does not include 1½" (35 mm) for door handles. *Height does not include ¼" (7 mm) for leg levelers.

‡ Cord length listed represents usable cord length.













TBR52-RISZ1-L-S-GG-1

True Bar Refrigerator • Reach-in single zone refrigerator

ADDITIONAL FEATURES

Refrigeration System

- Factory engineered, self-contained, capillary tube system.
- Environmentally friendly R290 hydrocarbon refrigerant.
- Forced air refrigeration system which maintains 33°F to 38°F (.5°C to 3.3°C) product temperatures.
- True's self-cleaning RCU technology eliminates the need to clean the condenser coil, reduces energy consumption and helps maintain the coldest temperatures and freshest product.

Cabinet Construction

- Exterior: Stainless steel front, sides and countertop.
- Interior: Stainless steel floor and sides with ABS plastic ceiling.
- Insulation: Entire cabinet is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion and zero global warming potential.
- · Base fitted with leg levelers.

Doors

- · Low-E, double pane thermal insulated glass doors.
- Door locks standard in countertop.
- Field Reversible Doors standard (reverse hinge kit included).

Shelving

- Three (3) adjustable, gray PVC coated wire shelves. 17¹¹/₁₆" W x 18" D (450 mm x 458 mm). Four (4) polished stainless steel shelf clips included per shelf.
- Aluminum shelf support pilasters. Shelves are adjustable on ½" (13 mm) increments.

Model Features

- NSF/ANSI Standard 7 compliant for open food product.
- · UL approved for outdoor use.
- · Electronic temp control with exterior digital display.
- Three (3) access ports standard (see drawing for locations).

Electrical

 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.


Optional TBR Features/Accessories


(upcharge and lead times may apply)


- ☐ Castors 7/8"H (23 mm) rollers, 2"D (51mm), 3"D (77mm), 4"D (102mm), 5"D (127mm) castors
- ☐ 6"H (153mm) legs
- ☐ 6"H (153mm) seismic legs
- \square Alternative temperature zones available (55° red wine, 45° white wine)
- ☐ Right side compressor
- $\hfill \square$ Shelving (wine, cut-out, additional standard wire, available in black or gray)
- ☐ Bottle Organizers (available in black or gray)
- ☐ Additional Access Ports
- ☐ Unit is available in a panel ready option which changes the nomenclature. Contact factory for details


PLAN VIEWS

Plan View Notes: Dimensions in brackets are in millimeters. Depth does not include 1½" (35 mm) for door handles. Height does not include ½" (7 mm) for leg levelers.









FRONT VIEW

SIDE VIEW

BACK VIEW

2001 East Terra Lane • O'Fallon, MO 63366-4434 • 636-240-2400 • Fax 636-272-2408 • Toll Free 800-325-6152 • Intl Fax 001-636-272-7546 • Parts Dept. 800-424-True • Parts Dept. Fax 636-272-9471 • truemfg.com