2001 East Terra Lane • O Fax (636)272-2408 • Toll Fr			Qty:	AIA #
Model: TFP-32-12M				
			TFP-32-12N	1

- True's food prep units are designed with enduring quality that protects your long term investment.
- Energy saving, environmentally friendly (R513A), exclusive forced-air refrigeration system holds 33°F to 41°F (.5°C to 5°C).
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Interior attractive, clear coated aluminum liner. Stainless steel floor with coved corners.
- ▶ 8" (204 mm) deep, ½" (13 mm) thick, full length removable cutting board included. Sanitary, high density white polyethylene provides tough preparation surface.
- Heavy-duty stainless steel drawer slides and rollers.
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

## ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest ½" (millimeters rounded up to next whole number).

			Pans	Cabinet Dimensions (inches) (mm)					NEMA	Cord Length (total ft.)	Crated Weight (lbs.)	
Model	Doors	Shelves	(top)	W	D†	H*	ΗP	Voltage	Amps	Config.	(total m)	(kg)
TFP-32-12M	1	2	12	321/8	31½	45¾	1⁄5	115/60/1	3.3	5-15P	7	315
				816	801	1162	N/A		N/A		2.13	143

† Depth does not include 2" (51 mm) for cutting board.

\* Height does not include <sup>3</sup>/<sub>4</sub>" (19 mm) for castors.

		APPROVALS:	AVAILABLE AT:
2/22	Printed in U.S.A.		

## Model:

## TFP-32-12M

# VI Food Prep Unit

# STANDARD FEATURES

## DESIGN

 True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.

## **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) R513A refrigerant.
- Energy saving, factory balanced refrigeration system with guided airflow to provide uniform temperature in food pans and cabinet interior.
- Exclusive forced-air design holds 33°F to 41°F (.5°C to 5°C) product temperature in food pans and cabinet interior. Complies with and listed under ANSI/NSF-7.
- High efficiency evaporator fan motor and larger fan blades give True Food Prep units a more efficient, low velocity, high volume airflow design.
- Easy access to all condensing unit components from back of cabinet.

WARRANTY

## **CABINET CONSTRUCTION**

- Exterior stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Interior attractive, clear coated aluminum liner. Stainless steel floor with coved corners.

## PLAN VIEW

- Insulation entire cabinet structure is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- 2<sup>1</sup>/<sub>2</sub>" (64 mm) diameter castors locks provided on front set.

## DOOR

**Food Prep Table:** 

- Stainless steel exterior with clear aluminum liner to match cabinet interior.
- Door fitted with 12" (305 mm) long recessed handle that is foamed-in-place with a sheet metal interlock to ensure permanent attachment.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

## SHELVING

- Two (2) adjustable, heavy duty PVC coated wire shelves 27 <sup>11</sup>/<sub>16</sub> "L x 20"D (703 mm x 508 mm). Four (4) chrome plated shelf clips included per shelf.
- Shelf support pilasters made of same material as cabinet interior; shelves are adjustable on ½" (13 mm) increments.

## **MODEL FEATURES**

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- 8" (204 mm) deep, full length removable cutting board. Sanitary, high-density white polyethylene provides tough preparation surface.



- Stainless steel, patented, foam insulated lid and hood keep pan temperatures colder, lock in freshness and minimize condensation. Removable for easy cleaning.
- Comes standard with 12 (% size) 6% "L x 6¼ "W x 4"D (175 mm x 159 mm x 102 mm) clear polycarbonate food pans in countertop prep area.
- Countertop pan opening designed to fit varying size pan configurations with available pan divider bars. Varying size pans supplied by others.
- NSF/ANSI Standard 7 compliant for open food product.

## **ELECTRICAL**


 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



## **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply. □ Pan dividers

- □ Single overshelf
- Double overshelf



Three year warranty on all parts and labor and an additional 2 year warranty on compressor. (U.S.A. only) Model SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

METRIC DIMENSIONS ROUNDED UP TO THE							
NEAREST WHOLE MILLIMETER	KCL	Model	Elevation	Right	Plan	3D	Back
SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE		TFP-32-12M					

## **TRUE MANUFACTURING CO., INC.**

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com