# TRUE MANUFACTURING CO., INC. U.S.A. FOODSERVICE DIVISION

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com Location: \_ Item #: \_\_\_\_

Model #:

Project Name:

<i>Qty:</i>	SIS #

Model: TPP-AT2-93D-6-HC Food Prep Table:

Solid Drawers Pizza Prep Table with Angled Top & Hydrocarbon Refrigerant



# TPP-AT2-93D-6-HC

AIA #

- True's pizza prep tables are designed with enduring quality that protects your long term investment.
- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydro carbon refrigerant that has zero (0) ozone depletion potential (ODP), & 0.02 global warming potential (GWP).
- High capacity, factory balanced environmentally friendly forced-air refrigeration system holds 33°F to 41°F (.5°C to 5°C).
- NSF/ANSI Standard 7 compliant for open food product.
- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Stainless steel, patented, foam insulated flat lids keep pan temperatures colder, lock in freshness, and minimize condensation.
- Interior attractive, clear coated aluminum liner. Stainless steel floor with coved corners.
- Extra-deep 19<sup>1</sup>/<sub>2</sub>" (496 mm) full length removable cutting board included. Sanitary, high density, white polyethylene provides tough preparation surface.
- Each drawer accommodates two (2) full size 12"L x 20"W x 8"D (305 mm x 508 mm x 204 mm) pans (sold separately).
- Foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).

(total ft.)

(total m)

10

3.05

▲ Plug type varies by country.

(lbs.)

(kg)

600

273

NEMA

Config.

5-15P

▲

# ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest ½" (millimeters rounded up to next whole number).								
2	Cabinet Dimensions (inches) (mm)					Cord Length	Crated Weight	

ΗP Model Drawers W D† H\* Voltage Amps (top) TPP-AT2-93D-6-HC 6 12 93% 335% 381/8 3⁄4 115/60/1 7.1 230-240/50/1 854 3.3 2372 987 1/2 + Depth does not include 1" (26 mm) for rear bumpers and 1¾" (44 mm) for cutting board.

\* Height does not include 1 (26 mm) for rear bumpers and 1% (44 mm) for cutting board \* Height does not include 5¾" (146 mm) for castors or 6" (153 mm) for optional legs.

Pans

MADE WITH INNOVATION COULS OF CECONATURAL IN THE USA	APPROVALS:	AVAILABLE AT:	
8/23 Printed in U.S.A.			

## Model:

#### Food Prep Table: Solid Drawers Pizza Prep Table with Angled Top TPP-AT2-93D-6-HC & Hydrocarbon Refrigerant



# STANDARD FEATURES

#### DESIGN

True's commitment to using the highest quality materials and oversized refrigeration systems provides the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.

### **REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly R290 hydrocarbon refrigerant that has zero (0) ozone depletion potential (ODP), & three (3) global warming potential (GWP).
- High capacity, factory balanced refrigeration system with guided airflow to provide uniform temperature in food pan rail and cabinet interior.
- Forced-air design holds 33°F to 41°F (.5°C to 5°C) product temperature in food pans and cabinet interior. Complies with ANSI/NSF-7.
- Condensing unit accessed from behind front removable panel, slides out for easy maintenance.

### **CABINET CONSTRUCTION**

- All stainless steel front, top and ends. Corrosion resistant GalFan coated steel back.
- Stainless steel, patented, foam insulated flat lids keep pan temperatures colder, lock in freshness, and minimize condensation.
- Interior attractive, clear coated aluminum liner. Stainless steel floor with coved corners.

# PLAN VIEW

- · Insulation entire cabinet structure and drawer facings are foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- 5" (127 mm) diameter stem castors. 36" (915 mm) work surface height.

#### DRAWERS

- Stainless steel exterior drawer facings and liners. Stainless steel drawer frames.
- Each drawer fitted with 12" (305 mm) long recessed handle that is foamed-in-place with a sheet metal interlock to ensure permanent attachment.
- Magnetic drawer gaskets of one piece construction, removable without tools for ease of cleaning.
- Heavy-duty stainless steel drawer slides and rollers. Removable without tools for easy cleaning.
- Each drawer accommodates two (2) full size 12"L x 20"W x 8"D (305 mm x 508 mm x 204 mm) food pans (sold separately). Drawer will support varying pan configurations with pan dividers bars (drawer pans and divider bars optional).

#### **MODEL FEATURES**

- Evaporator is epoxy coated to eliminate the potential of corrosion.
- Extra-deep 191/2" (496 mm), full length removable cutting board included. Sanitary, high-density, white polyethylene provides tough preparation surface.
- Angled top 13° pan angle. Stainless steel, patented, foam insulated lids keep pan temperatures colder, lock in freshness, and minimize condensation.

- Refrigerated pan rail comes standard with twelve (1/3 size) 12 3/4 "L x 6 1/4" W x 6"D (324 mm x 159 mm x 153 mm) NSF approved clear polycarbonate insert pans.
- Front discharge design.
- NSF/ANSI Standard 7 compliant for open food product.

#### **ELECTRICAL**


Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.



## **OPTIONAL FEATURES/ACCESSORIES**

Upcharge and lead times may apply. 230 - 240V / 50 Hz.

- G" (153 mm) standard legs.
- □ 6" (153 mm) seismic/flanged legs.
- □ 4" (102 mm) diameter castors.
- 3" (85 mm) diameter castors.
- 2½" (64 mm) diameter castors.
- Garnish racks.
- □ 19½" (496 mm) deep, ½" (13 mm) thick, composite cutting board.
- Pan dividers.
- Exterior digital temperature display (factory installed).



METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

MAN	Model	Elevation	Right	Plan	3D	Back
KCL	TPP-AT2-93D-6-HC					

## **TRUE MANUFACTURING CO., INC.**

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 • Fax (636)272-2408 • Toll Free (800)325-6152 • Intl. Fax# (001)636-272-7546 • www.truemfg.com